

Package ‘JMI’

October 19, 2018

Type Package

Title Jackknife Mutual Information

Version 0.1.0

Author Zeng Xianli <a0123862@u.nus.edu>, Hang Weiqiang <e0010758@u.nus.edu>

Maintainer Zeng Xianli <a0123862@u.nus.edu>

Description Computes the Jackknife Mutual Information (JMI) between two random vectors and provides the p-value for dependence tests. See Zeng, X., Xia, Y. and Tong, H. (2018) <doi:10.1073/pnas.1715593115>.

License GPL (>= 2)

Encoding UTF-8

LazyData true

Imports Rcpp

LinkingTo Rcpp, RcppArmadillo

RoxygenNote 6.0.1

NeedsCompilation yes

Repository CRAN

Date/Publication 2018-10-19 15:10:12 UTC

R topics documented:

JMI	2
Index	3

JMI

Jackknife Mutual Information

Description

This function provides method for dependence test. It uses permutation test to determine the rejection region.

Usage

```
JMI(x, y, BN = 1000)
```

Arguments

x	n by p sample matrix.
y	n by q sample matrix.
BN	Number of permutations, the default value is 1000.

Value

the output is a list which contains:

- mi: the value of Jackknife Mutual information
- pvalue: the p-value of independence test that based on the permutation of JMI, the value is not provided if BN=0.

References

Zeng, X., Xia, Y., & Tong, H. (2018). Jackknife approach to the estimation of mutual information[J]. Proceedings of the National Academy of Sciences, 201715593.

Examples

```
x <- matrix(rnorm(50*3),50,3)
y <- matrix(rnorm(50*2),50,2)
#calculate the Jackknife Mutual information between x and y.
JMI(x,y,0)$mi
#calculate the p-value of independent test between x and y that based on 500 permutations.
JMI(x,y,500)$pvalue
```

Index

JMI, [2](#)