

Package ‘qad’

December 2, 2021

Type Package

Title Quantification of Asymmetric Dependence

Version 1.0.1

Description A copula-based measure for quantifying asymmetry in dependence and associations. Documentation and theory about 'qad' is provided by the paper by Junker, Griessenberger & Trutschnig (2021, <[doi:10.1016/j.csda.2020.107058](https://doi.org/10.1016/j.csda.2020.107058)>), and the paper by Trutschnig (2011, <[doi:10.1016/j.jmaa.2011.06.013](https://doi.org/10.1016/j.jmaa.2011.06.013)>).

License GPL-2

URL <https://github.com/grieffl/qad>

BugReports <https://github.com/grieffl/qad/issues>

Encoding UTF-8

Depends R (>= 2.10)

Imports ggplot2, data.table, copula, viridis, ggExtra, dplyr, cowplot,
Rcpp (>= 1.0.6)

RoxygenNote 7.1.2

LinkingTo Rcpp

Suggests rmarkdown, reshape2, knitr, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

NeedsCompilation yes

Author Florian Griessenberger [aut, cre],
Robert R. Junker [aut],
Valentin Petzel [aut],
Wolfgang Trutschnig [aut]

Maintainer Florian Griessenberger <florian.griessenberger@sbg.ac.at>

Repository CRAN

Date/Publication 2021-12-02 14:30:02 UTC

R topics documented:

qad-package	2
D1	3
ECBC	5
emp_c_copula	6
heatmap.qad	8
pairwise.qad	9
plot.qad	11
plot_density	12
predict.qad	13
qad	15
qad_distribution	18
summary.qad	19
Index	20

qad-package	<i>Quantification of Asymmetric Dependencies</i>
-------------	--------------------------------------------------

Description

A copula-based measure for quantifying asymmetry in dependence and associations.

Details

Package: qad
 Type: Package
 Version: 1.0.0
 Date: 2021-02-26

Author(s)

Florian Griessenberger: <florian.griessenberger@sbg.ac.at>,
 Robert R. Junker: <Robert.Junker@sbg.ac.at>,
 Valentin Petztl,
 Wolfgang Trutschnig: <Wolfgang.Trutschnig@sbg.ac.at>

Examples

```
# #Create data set
# n <- 100
# x <- rnorm(n,0,2)
# y <- x^2 + rnorm(n)
# sample <- data.frame(x,y)
```

```

# plot(sample, pch = 16)
#
#
# #Function: qad()
# qad(sample, p.value = TRUE, p.value_asymmetry = TRUE)
# fit <- qad(sample)
# plot(fit)
# plot(fit, copula = TRUE)
# plot(fit, copula = TRUE, addSample = T)
#
# #Functions: summary(), coef()
# summary(fit)
# coef(fit)
#
# #Function: predict()
# values <- c(-2.4,1,0,2.6)
# predict.qad(fit, values = values, conditioned = 'x1')
# predict(fit, values, conditioned = "x1", pred_plot = TRUE, panel.grid = FALSE)
#
# values <- c(0.1,0.5)
# predict(fit, values, conditioned = "x2", copula = TRUE, pred_plot = TRUE)
#
# #Function: pairwise.qad and heatmap.qad
# df <- iris[1:4]
# mod <- pairwise.qad(df)
# heatmap.qad(mod, select = 'dependence')

```

D1

Calculate the D1 distance between two dependence structures

Description

Computation of the D1 distance between two checkerboard copulas A and B, corresponding to the random vectors (X1,Y1) and (X2,Y2), respectively. The function `D1()` computes the difference between the dependence structures of two random vectors. The function `D1.ECBC()` computes the D1-distance between two checkerboard copulas with the same resolution. The function `zeta1()` is defined as $3D1(A, \Pi)$, where Π denotes the independence copula and returns the dependence measure computed in `qad`.

Usage

```
D1(x1, y1, x2, y2, resolution = NULL)
```

```
D1.ECBC(A, B)
```

```
zeta1(X, Y, resolution = NULL)
```

Arguments

x1	a (non-empty) numeric vector of data values for the first random vector (first coordinate)
y1	a (non-empty) numeric vector of data values for the first random vector (second coordinate)
x2	a (non-empty) numeric vector of data values for the second random vector (first coordinate)
y2	a (non-empty) numeric vector of data values for the second random vector (second coordinate)
resolution	integer indicating the resolution of the checkerboard copula. (default = NULL)
A	Numeric matrix of dimension $N \times N$ indicating the mass of the first N-checkerboard copula
B	Numeric matrix of dimension $N \times N$ indicating the mass of the second N-checkerboard copula
X	Numeric vector of values in the first coordinate
Y	Numeric vector of values in the second coordinate

Value

D1() returns the D1 distance, introduced in (Trutschnig, 2011).

D1.ECBC() returns the D1-distance between to checkerboard copulas A and B with same resolution

zeta1() returns the directed dependence from x to y.

References

Trutschnig, W. (2011). On a strong metric on the space of copulas and its induced dependence measure. *Journal of Mathematical Analysis and Applications*. 384 (2), 690-705.

Junker, R.R., Griessenberger, F. and Trutschnig, W. (2021). Estimating scale-invariant directed dependence of bivariate distributions. *Computational Statistics and Data Analysis*, 153, 107058.

Examples

```
n <- 100
x1 <- runif(n)
y1 <- x1
x2 <- runif(n)
y2 <- 1-x2
D1(x1,y1,x2,y2)
```

```
n <- 1000
x <- runif(n, 0, 1)
y1 <- ifelse(x < 0.5, runif(length(x < 0.5), 0,0.5), runif(length(x >= 0.5), 0.5, 1))
y2 <- ifelse(x > 0.5, runif(length(x < 0.5), 0,0.5), runif(length(x >= 0.5), 0.5, 1))
A <- ECBC(x,y1, resolution = 50)
B <- ECBC(x,y2, resolution = 50)
```

```
#plot_density(A)
#plot_density(B)
D1.ECBC(A,B)
```

 ECBC

Calculate empirical checkerboard copula

Description

The function ECBC() computes the mass distribution of the empirical (checkerboard) copula, given a bi-variate sample. If resolution equals sample size, the bi-linearly extended empirical copula is returned. Note, if there are ties in the sample an adjusted empirical copula is calculated. The function ECBC.eval() evaluates the checkerboard copula at given points.

Usage

```
ECBC(X, Y, resolution = NULL)
```

```
ECBC.eval(CB, eval.points)
```

Arguments

X	Numeric vector of values in the first coordinate
Y	Numeric vector of values in the second coordinate
resolution	Integer indicating the resolution of the checkerboard aggregation, i.e. the number of vertical/horizontal strips of the checkerboard copula. (default = NULL, sets resolution = floor(sqrt(sample size)))
CB	A numeric mass matrix of a checkerboard copula (ECBC)
eval.points	A numeric matrix or data.frame indicating the eval.points (x,y)

Details

If the observations are drawn from a continuous distribution (no ties in the sample), the function ECBC() returns the commonly used empirical checkerboard copula. If there are ties in the sample, the empirical copula is adjusted and calculated in the following way:

Let $(u_i, v_i) := (F_n(x_i), G_n(y_i))$ be the pseudo-observations for i in $\{1, \dots, n\}$ and $(u_{1'}, v_{1'}), \dots, (u_{m'}, v_{m'})$ the distinct pairs of pseudo-observations with $m \leq n$. Moreover set $S_{-1} := \{0, u_1, \dots, u_{m-1}\}$ and $S_{-2} := \{0, v_1, \dots, v_{m-2}\}$ and define the quantities t_i, r_i and s_i for $i=1, \dots, m$ by

$$t_i := \sum_{j=1}^n 1_{(u_i', v_i')}(u_j, v_j)$$

$$r_i := \sum_{j=1}^n 1_{u_i}(u_j)$$

$$s_i := \sum_{j=1}^n 1_{v_i}(v_j)$$

where 1 defines the indicator function. Define the empirical subcopula $A'_n: S_{-1} \times S_{-2}$ to $\{0, 1/n, \dots, (n-1)/n, 1\}$ by

$$A'_n(s_1, s_2) = 1/n \sum_{i=1}^m t_i * 1_{[0, s_1] \times [0, s_2]}(u_i', v_i') = 1/n \sum_{i=1}^n 1_{[0, s_1] \times [0, s_2]}(u_i, v_i)$$

for all s_1 in S_1 and s_2 in S_2 .

We extend the subcopula A'_n to a copula by defining the transformations $w_i: [0,1]^2$ to $[u_i' - r_i/n, u_i'] \times [v_i' - s_i/n, v_i']$ by

$$w_i(x, y) = (u_i' - r_i/n + r_i * x/n, v_i' - s_i/n + s_i y/n)$$

and set the measure of the empirical copula $\mu_{A_n} \wedge B := 1/n \sum_{i=1}^m t_i \mu_B \wedge w_i$, where B denotes the product copula.

Value

ECBC() returns a matrix with the mass distribution of the empirical (checkerboard) copula.

References

Deheuvels, P. (1979). La fonction de dependance empirique et ses proprietas: un test non parametrique d'independance, Acad. Roy. Belg. Bull. Cl. Sci., 5th Ser. 65, 274-292.

Li, X., Mikusinski, P. and Taylor, M.D. (1998). Strong approximation of copulas, Journal of Mathematical Analysis and Applications, 255, 608-623.

Genest, C., Neshlehova J.G. and Remillard, B. (2014). On the empirical multilinear copula process for count data. Bernoulli, 20 (3), 1344-1371.

Junker, R.R., Griessenberger, F. and Trutschnig, W. (2021). Estimating scale-invariant directed dependence of bivariate distributions. Computational Statistics and Data Analysis, 153, 107058.

Examples

```
##Generate data drawn from the product copula and compute the empirical (checkerboard) copula
n <- 100
x <- runif(n, 0, 1)
y <- runif(n, 0, 1)
mass <- ECBC(x,y, resolution = 10)
plot_density(mass)
mass <- ECBC(x,y, resolution = n)
plot_density(mass)

## Compute empirical checkerboard copula of a sample with ties and plot density
n <- 100
x <- sample(runif(n, -1, 1), n, replace=TRUE)
y <- x^2 + rnorm(n, 0, 1)
mass <- ECBC(x,y)
plot_density(mass)
```

Description

The function `emp_c_copula()` computes the mass distribution of the empirical (checkerboard) copula, given a bivariate sample. `emp_c_copula_eval()` evaluates the the empirical (checkerboard) copula at given points. If `smoothing = FALSE`, the empirical copula is computed (if there are ties in the sample an adjusted empirical copula is computed), otherwise the empirical checkerboard copula - a smoothed version of the empirical copula - is computed. For more information of the calculations, see details.

Usage

```
emp_c_copula(X, smoothing = TRUE, resolution)
```

```
emp_c_copula_eval(X, u, smoothing = TRUE, resolution)
```

Arguments

<code>X</code>	a data frame with two columns containing the observations of the sample. Each row contains one observation.
<code>smoothing</code>	a logical indicating whether the checkerboard aggregation is computed (default = TRUE).
<code>resolution</code>	an integer indicating the resolution of the checkerboard aggregation, i.e. the number of vertical/horizontal strips of the checkerboard copula.
<code>u</code>	a data.frame with two columns containing the evaluation points. Each row consists of a x and y value.

Details

If the observations come from a distribution with continuous margins, i.e. there are no ties in the sample, the function `emp_c_copula()` gives the same result as the function `C.n()` in the `copula` package. If there are ties in the sample, the empirical copula is adjusted and calculated in the following way:

Let $(u_i, v_i) := (F_n(x_i), G_n(y_i))$ be the pseudo-observations for i in $\{1, \dots, n\}$ and $(u_1', v_1'), \dots, (u_m', v_m')$ the distinct pairs of pseudo-observations with $m \leq n$. Moreover set $S_1 := \{0, u_1, \dots, u_m\}$ and $S_2 := \{0, v_1, \dots, v_m\}$ and define the quantities t_i, r_i and s_i for $i=1, \dots, m$ by

$$\begin{aligned} t_i &:= \sum_{j=1}^n \mathbf{1}_{(u_i', v_i)}(u_j, v_j) \\ r_i &:= \sum_{j=1}^n \mathbf{1}_{u_i}(u_j) \\ s_i &:= \sum_{j=1}^n \mathbf{1}_{v_i}(v_j) \end{aligned}$$

where $\mathbf{1}$ defines the indicator function. Define the empirical subcopula $A'_n: S_1 \times S_2$ to $\{0, 1/n, \dots, (n-1)/n, 1\}$ by

$$A'_n(s_1, s_2) = 1/n \sum_{i=1}^m t_i * \mathbf{1}_{[0, s_1] \times [0, s_2]}(u_i', v_i) = 1/n \sum_{i=1}^m \mathbf{1}_{[0, s_1] \times [0, s_2]}(u_i, v_i)$$

for all s_1 in S_1 and s_2 in S_2 .

We extend the subcopula A'_n to a copula by defining the transformations $w_i: [0, 1]^2$ to $[u_i' - r_i/n, u_i'] \times [v_i' - s_i/n, v_i']$ by

$$w_i(x, y) = (u_i' - r_i/n + r_i * x/n, v_i' - s_i/n + s_i y/n)$$

and set the measure of the empirical copula $\mu_{A_n \wedge B} := 1/n \sum_{i=1}^m t_i \mu_{B \wedge w_i}$, where B denotes the product copula.

The checkerboard aggregation is computed as usual (see references).

Value

`emp_c_copula()` returns a matrix with the mass distribution of the empirical (checkerboard) copula.

`emp_c_copula_eval()` returns a vector of evaluations of the empirical (checkerboard) copula.

Note

The calculation of the empirical copula with a high sample size (and resolution rate) can take time.

References

Deheuvels, P. (1979). La fonction de dependance empirique et ses proprietes: un test non parametrique d'independance, Acad. Roy. Belg. Bull. Cl. Sci., 5th Ser. 65, 274-292.

Li, X., Mikusinski, P. and Taylor, M.D. (1998). Strong approximation of copulas, Journal of Mathematical Analysis and Applications, 255, 608-623.

Genest, C., Neshlehova J.G. and Remillard, B. (2014). On the empirical multilinear copula process for count data. Bernoulli, 20 (3), 1344-1371.

heatmap.qad

Heatmap of dependence measures

Description

The pairwise computed dependence measures (output of the function `pairwise.qad()`) are illustrated by a heatmap.

Usage

```
heatmap.qad(
  pw_qad,
  select = c("dependence", "max.dependence", "asymmetry"),
  fontsize = 4,
  significance = FALSE,
  sign.level = 0.05,
  scale = "abs",
  color = "plasma",
  rb_values = c(10, 0.315, 0.15),
  title = ""
)
```

Arguments

<code>pw_qad</code>	output of the function <code>pairwise.qad()</code> .
<code>select</code>	a character indicating which dependence value is plotted. Options are <code>c("dependence", "max.dependence", "asymmetry")</code> .
<code>fontsize</code>	a numeric specifying the font size of the values.
<code>significance</code>	a logical indicating whether significant values - with respect to the qad p.values - are denoted by a star.
<code>sign.level</code>	numeric value indicating the significance level.
<code>scale</code>	character indicating whether the heatmap uses a relative or absolute scale. Options are <code>"rel"</code> or <code>"abs"</code> (default).
<code>color</code>	Select the color palette. Options are <code>c("plasma" (default), "viridis", "inferno", "magma", "cividis")</code> .
<code>rb_values</code>	a vector of size 3 with number of values, start value and end value in the rainbow colors space.
<code>title</code>	The text for the title

Details

If the output of `pairwise.qad()` contains p-values, significant values can be highlighted by stars by setting `significance=TRUE`.

Value

a heatmap

Examples

```
n <- 100
x1 <- runif(n, 0, 1)
x2 <- x1^2 + rnorm(n, 0, 0.1)
x3 <- runif(n, 0, 1)
x4 <- x3 - x2 + rnorm(n, 0, 0.1)
sample_df <- data.frame(x1,x2,x3,x4)
#Fit qad
model <- pairwise.qad(sample_df, p.value = FALSE)
heatmap.qad(model, select = "dependence", fontsize = 6)
```

`pairwise.qad`

Pairwise quantification of (asymmetric and directed) dependencies

Description

Pairwise computation of the function `qad()`. `qad()` is applied on each pair of variables of a numeric `data.frame`.

Usage

```
pairwise.qad(
  data_df,
  remove.00 = FALSE,
  min.res = 3,
  p.value = TRUE,
  nperm = 1000,
  p.value_asymmetry = FALSE,
  nboot = 1000
)
```

Arguments

<code>data_df</code>	a data frame containing numeric columns with the observations of the sample.
<code>remove.00</code>	a logical indicating whether double 0 entries should be excluded (default = FALSE)
<code>min.res</code>	an integer indicating the necessary minimum resolution of the checkerboard grid to compute qad, otherwise the result is NA (default = 3).
<code>p.value</code>	a logical indicating whether to return a p-value of rejecting independence (based on permutation).
<code>nperm</code>	an integer indicating the number of permutation runs.
<code>p.value_asymmetry</code>	a logical indicating whether a p-value (based on bootstrap) is computed for the measure of asymmetry.
<code>nboot</code>	an integer indicating the number of bootstrapping runs.

Value

a list, containing 8 data.frames with the dependence measures, corresponding p.values, the resolution of the checkerboard aggregation and the number of removed double zero entries (only if `remove.00 = TRUE`). The output of `pairwise.qad()` can be illustrated using the function `heatmap.qad()`.

Examples

```
n <- 100
x1 <- runif(n, 0, 1)
x2 <- x1^2 + rnorm(n, 0, 0.1)
x3 <- runif(n, 0, 1)
x4 <- x3 - x2 + rnorm(n, 0, 0.1)
sample_df <- data.frame(x1,x2,x3,x4)
#Fit qad
model <- pairwise.qad(sample_df, p.value = FALSE)
heatmap.qad(model, select = "dependence", fontsize = 6)
```

plot.qad	<i>Plot conditional probabilities</i>
----------	---------------------------------------

Description

Visualizes the conditional probabilities for each strip of the checkerboard copula in the copula setting or in the retransformed sample setting.

Usage

```
## S3 method for class 'qad'
plot(
  x,
  addSample = FALSE,
  copula = FALSE,
  density = FALSE,
  margins = FALSE,
  title = "",
  x.axis = "X1",
  y.axis = "X2",
  point.size = 0.9,
  panel.grid = TRUE,
  color = "plasma",
  rb_values = c(10, 0.315, 0.15),
  ...
)
```

Arguments

x	an object of class qad.
addSample	a logical indicating whether the observations are returned. In the copula setting the mass squares of the empirical copula are added too. (default = FALSE).
copula	a logical indicating whether the plot depicts the conditional probabilities of the empirical checkerboard copula or of the retransformed data setting (default = FALSE).
density	a logical indicating whether the density should be plotted instead of the conditional probabilities (default = FALSE). Only works in the copula setting, i.e. if copula = TRUE.
margins	a logical indicating whether the margin distribution is added in form of a rug plot.
title	The text for the title
x.axis	The text for the x-axis
y.axis	The text for the y-axis
point.size	a numeric specifying the point size of the sample (relevant if addSample = TRUE).

panel.grid	a logical indicating whether the panel grid is plotted. (default = TRUE)
color	a color palette of the viridis package or rainbow. options are c("viridis", "magma", "inferno", "plasma", "cividis", "rainbow")
rb_values	a vector of size 3 with number of values, start value and end value in the rainbow colors space.
...	some methods for this generic require additional arguments. None are used in this method.

Note

The conditional probabilities are constant at squares in the copula setting. If the squares are retransformed in the data setting, the resulting objects are rectangles.

Examples

```
## Example 1
n <- 100
x <- runif(n, 0, 1)
y <- runif(n, 0, 1)
sample <- data.frame(x, y)

#qad
fit <- qad(sample)
plot(fit, addSample = TRUE, copula = FALSE)

## Example 2
n <- 100
x <- runif(n, -1, 1)
y <- x^2 + rnorm(n, 0, 0.1)
sample <- data.frame(x, y)

#qad
fit <- qad(sample)
plot(fit, addSample = TRUE, copula = TRUE)
plot(fit, addSample = TRUE, copula = FALSE)
```

plot_density

Plot density of empirical checkerboard copula

Description

Plots the density/mass of the empirical checkerboard copula.

Usage

```
plot_density(  
  mass_matrix,  
  density = TRUE,  
  color = "plasma",  
  rb_values = c(10, 0.315, 0.15)  
)
```

Arguments

mass_matrix	a squared matrix containing the mass distribution, e.g. output of the function <code>emp_c_copula()</code> .
density	a logical (TRUE = default) whether the density or the mass is plotted.
color	Select the color palette. Options are <code>c("plasma" (default), "viridis", "inferno", "magma", "cividis")</code> .
rb_values	a vector of size 3 with number of values, start value and end value in the rainbow colors space.

Value

a density plot (or mass distribution)

Examples

```
n <- 1000  
x <- runif(n,0,1)  
y <- runif(n,0,1)  
plot(x,y,pch = 16)  
  
mass <- ECBC(x,y,resolution = 10)  
plot_density(mass, density=TRUE)  
plot_density(mass, density=FALSE)
```

Description

The function `predict.qad()` can be utilized to predict the probabilities of the event that Y lies in specific intervals given $X=x$, or vice versa. Additionally, the mass of the conditional distribution functions are plotted. The prediction can be computed in the sample setting as well as in the copula setting (pseudo-observation in the unit square).

Usage

```
## S3 method for class 'qad'
predict(
  object,
  values,
  conditioned = "x1",
  nr_intervals = NULL,
  prediction_interval = NULL,
  copula = FALSE,
  pred_plot = FALSE,
  panel.grid = TRUE,
  ...
)
```

Arguments

object	an object of class 'qad', which determines the underlying checkerboard aggregation.
values	a vector containing the x or the y values for which the conditional probabilities should be predicted.
conditioned	a character specifying on which variable is conditioned. Options are "x1" (default) or "x2".
nr_intervals	an integer, which determines a different number of intervals for the prediction (only possible in the copula setting).
prediction_interval	a vector specifying the interval boundaries for which the conditional probability is computed. Options are NULL (default) to predict the conditional probabilities for all intervals or a vector c(lower_boundary, upper_boundary) indicating the boundaries.
copula	a logical (default =FALSE) determining whether the empirical checkerboard copula is used or the retransformed data.
pred_plot	a logical indicating if the conditional probabilities are plotted.
panel.grid	a logical indicating whether the panel.grid is plotted.
...	some methods for this generic require additional arguments. None are used in this method.

Value

a list containing a data.frame with the interval boundaries and the prediction probabilities and a plot depicting the mass of the conditional distributions functions.

Note

Predictions are only possible for values within the range of the sample (or between 0 and 1 in the copula setting). For given values exceeding the range NA is returned.

Examples

```

set.seed(1)
n <- 100
x <- runif(n, -4 ,4)
y <- x^2 + rnorm(n, 0, 1)
sample <- data.frame(x, y)

##(Not Run)
qad.fit <- qad(sample)
predict.qad(qad.fit, values = c(-2,0.6), conditioned = "x1", pred_plot = TRUE)
predict.qad(qad.fit, values = c(1,9), conditioned = "x2", pred_plot = TRUE)
predict.qad(qad.fit, values = c(-2,0.6), conditioned = "x1", pred_plot = FALSE,
            nr_intervals = 4)
predict.qad(qad.fit, values = c(-2,0.6), conditioned = "x1", pred_plot = FALSE,
            prediction_interval = c(4,6))
predict.qad(qad.fit, values = c(4,0.6), conditioned = "x2", pred_plot = FALSE,
            prediction_interval = c(2,3))

qad.pred <- predict.qad(qad.fit, values = c(-2,0.6), conditioned = "x1", pred_plot = FALSE)
qad.pred$prediction
qad.pred$plot

```

qad

Measure of (asymmetric and directed) dependence

Description

Quantification of (asymmetric and directed) dependence structures between two random variables X and Y.

Usage

```

qad(x, ...)

## S3 method for class 'data.frame'
qad(
  x,
  resolution = NULL,
  p.value = TRUE,
  nperm = 1000,
  p.value_asymmetry = FALSE,
  nboot = 1000,
  print = TRUE,
  remove.00 = FALSE,
  ...
)

```

```
## S3 method for class 'numeric'
qad(
  x,
  y,
  resolution = NULL,
  p.value = TRUE,
  nperm = 1000,
  p.value_asymmetry = FALSE,
  nboot = 1000,
  print = TRUE,
  remove.00 = FALSE,
  ...
)
```

Arguments

<code>x</code>	a data.frame containing two columns with the observations of the bi-variate sample or a (non-empty) numeric vector of data values
<code>...</code>	Further arguments passed to 'qad' will be ignored
<code>resolution</code>	an integer indicating the number of strips for the checkerboard aggregation (see ECBC). We recommend to use the default value (<code>resolution = NULL</code>)
<code>p.value</code>	a logical indicating whether to return a p-value of rejecting independence (based on permutation).
<code>nperm</code>	an integer indicating the number of permutation runs (if <code>p.value = TRUE</code>)
<code>p.value_asymmetry</code>	a logical indicating whether to return a p-value for the measure of asymmetry (based on bootstrap).
<code>nboot</code>	an integer indicating the number of runs for the bootstrap.
<code>print</code>	a logical indicating whether the result of qad is printed.
<code>remove.00</code>	a logical indicating whether double 0 entries should be excluded (default = <code>FALSE</code>)
<code>y</code>	a (non-empty) numeric vector of data values.

Details

qad is the implementation of a strongly consistent estimator of the copula based dependence measure ζ_1 introduced in Trutschnig 2011. We first compute the empirical copula of a two-dimensional sample, aggregate it to the so called empirical checkerboard copula (ECBC), and calculate ζ_1 of the ECBC and its transpose. In order to test for independence (in both directions), a built-in p-value is implemented (a permutation test with `nperm` permutation runs to estimate the p-value). Furthermore, a bootstrap test with `nboot` runs can be applied to estimate a p-value for the measure of asymmetry a .

Value

qad returns an object of class qad containing the following components:

data	a data.frame containing the input data.
q(X,Y)	influence of X on Y
q(Y,X)	influence of Y on X
max.dependence	maximal dependence
results	a data.frame containing the results of the dependence measures.
mass_matrix	a matrix containing the mass distribution of the empirical checkerboard copula.
resolution	an integer containing the used resolution of the checkerboard aggregation.
n	Sample size.

References

Trutschnig, W. (2011). On a strong metric on the space of copulas and its induced dependence measure, *Journal of Mathematical Analysis and Applications* 384, 690-705.

Junker, R., Griessenberger, F. and Trutschnig, W. (2021). Estimating scale-invariant directed dependence of bivariate distributions. *Computational Statistics and Data Analysis*, 153.

See Also

A tutorial can be found at <http://www.trutschnig.net/software.html>.

Examples

```
#Example 1 (independence)

n <- 100
x <- runif(n,0,1)
y <- runif(n,0,1)
sample <- data.frame(x,y)
qad(sample)

###

#Example 2 (mutual complete dependence)

n <- 500
x <- runif(n,0,1)
y <- x^2
sample <- data.frame(x,y)
qad(sample)

#Example 3 (complete dependence)

n <- 1000
x <- runif(n,-10,10)
y <- sin(x)
```

```

sample <- data.frame(x,y)
qad(sample)

#Example 4 (Asymmetry)

n <- 100
x <- runif(n,0,1)
y <- (2*x) %% 1
qad(x, y, p.value_asymmetry = TRUE)

```

qad_distribution *Distribution of qad (H0: independence)*

Description

Distribution function - $P_{H0}(qad \leq q)$ - and quantile function for the qad distribution with regard to the null hypothesis (H_0) stating independence between X and Y .

Usage

```

pqad(q, n, R = 1000, resolution = NULL)

qqad(p, n, R = 1000, resolution = NULL)

```

Arguments

q	vector of quantiles.
n	number of observations (or minimum of unique values, if ties occur).
R	number of repetitions (default $R = 1000$)
resolution	resolution of checkerboard copula (default = NULL)
p	vector of probabilities.

Details

The distribution of qad in the setting of independence, i.e., the random variables X and Y are independent. The distribution is calculated in the following way: Samples of size n are drawn from independent random variables. Then qad is calculated. The procedure is repeated R times. #'

Value

pqad gives the distribution function, i.e. $P(qad \leq q)$. qqad gives the quantile function. The length of the result is determined by the length of q or p , respectively.

Examples

```

pqad(0.3, 45)
qqad(0.5, 30)

```

summary.qad

*Summarize a qad object***Description**

Summary and coefficients of a qad output. The function `summary()` prints the dependence measures, sample size and resolution of the checkerboard copula and returns a list with the mentioned values. The function `coef()` returns a named vector with the selected values.

Usage

```
## S3 method for class 'qad'
summary(object, ...)

## S3 method for class 'qad'
coef(
  object,
  select = c("q(x1,x2)", "q(x2,x1)", "max.dependence", "asymmetry", "p.q(x1,x2)",
            "p.q(x2,x1)", "p.max.dependence", "p.asymmetry"),
  ...
)
```

Arguments

<code>object</code>	an object of class 'qad'
<code>...</code>	some methods for this generic require additional arguments. None are used in this method.
<code>select</code>	a vector of strings indicating which dependence measure should be returned. Options are <code>c('q(x1,x2)', 'q(x2,x1)', 'max.dependence', 'asymmetry')</code>

Value

an object containing the calculated values of a qad object.

Examples

```
n <- 100
x <- runif(n, 0, 1)
y <- x^2 + rnorm(n, 0, 0.1)
sample <- data.frame(x, y)
##(Not Run)
fit <- qad(sample)
summary(fit)
coef(fit)
coef(fit, select = c('q(x1,x2)', 'p.q(x1,x2)'))
```

Index

* package

qad-package, 2

coef.qad (summary.qad), 19

D1, 3

ECBC, 5, 16

emp_c_copula, 6

emp_c_copula_eval (emp_c_copula), 6

heatmap.qad, 8

pairwise.qad, 9

plot.qad, 11

plot_density, 12

pqad (qad_distribution), 18

predict.qad, 13

qad, 15

qad-package, 2

qad_distribution, 18

qqad (qad_distribution), 18

summary.qad, 19

zeta1 (D1), 3